Dial Reading Viscometer

our original…over 80 years!

The Worldwide Standard
Viscometer

Easy–to–Select Speeds

Electronic Drive
means quiet,
reliable operation

Analog display
- Shows % Torque
- Use Factor Finder to convert reading to centipoise

Simple-to-use,
easy setup

2–Year Limited Warranty

Available in explosion proof
U.L. Class 1, Division 1,
Group D locations
(w/o Electronic Drive)

Accuracy: ±1.0% of range

Repeatability: ±0.2%

What's Included?

Instrument
6 spindles (RV/HA/HB) (p45)
or 4 spindles (LV) (p45)
Spindle Guard Leg*
Lab Stand (Model A) (p50)
Carrying Case
*Not applicable to HA or HB torque models

Optional Accessories

Viscosity Standards (p52)
RV/HA/HB-1 Spindle (p45)
Quick Action Lab Stand (p50)
Temperature Bath (p33-35)
Small Sample Adapter (p38)
UL Adapter (p40)
Thermosel (p36)
Spiral Adapter (p44)
DIN Adapter (p44)
Quick Connect/Extension Links (p49)
Vane Spindles (p43 & 48)

	VISCOSITY RANGE cP(mPa•s)		SPEEDS	
MODEL	Min.	Max.	RPM	Number of Increments
LVT	1†	2M	.3-60	8
RVT	100††	8M	.5-100	10
HAT	200††	16M	.5-100	10
HBT	800††	64M	.5-100	10

† 1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.
†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.
M = 1 million cP = Centipoise mPa•s = Millipascal•seconds

Easy Speed Adjustment and On/Off Control

TEL 800-628-8139 or 508-946-6200 **FAX** 508-946-6262 **www.brookfieldengineering.com**